



# VISIONS

## Wet Look / Multi-Speed Floor Finish

### DESCRIPTION

An instant deep wet look thermoplastic floor finish which can be high speed burnished or maintained with conventional methods. This unique premium grade floor finish is manufactured in high pressure reactors using integrated latex and oligomeric polymer emulsions chemically combined with super high pressure micronized wax emulsions, interacted plasticizers, preservatives, coalescent additives, leveling aids, and deionized water to offer maximum performance.

### PRODUCT FEATURES / BENEFITS

- Immediate Wet Look; Offers high appearance level without buffing
- Designed for ease of application; May be applied by any personnel without extensive training.
- Flexible Film; Allows for easy removal of black heel marks and scratches; Can be high speed burnished on a daily maintenance schedule
- May be used with conventional or high speed floor maintenance system; Allows versatility and reduced inventory levels of additional products

### DIRECTIONS FOR USE

**Floor Preparation:** Strip old finish and wax using your preferred NCL floor stripper following label directions. For baseboards and corners, use an NCL baseboard stripper following label directions. If necessary, rinse thoroughly with clean water and allow to completely dry.

**Application:** Using a clean mop or applicator apply thin uniform coats of VISIONS™ Wet Look Floor Finish. Allow to dry for a minimum of 20 minutes after each coat. Do not apply more than 4 coats in a 24 hour period. Floor should be thoroughly dry before traffic is allowed in area.

**High Speed Buffing and Burnishing:** This is an ideal product for use with high speed polishing or burnishing machines of

1000 rpm or higher. Prior to high speed buffing or burnishing the floor surface should be dust mopped using preferred NCL dust mop treatment. When buffing or dry burnishing, use an approved Buffing Pad. For spray buffing and for mop-on restoring use VIVID™ Laminator & Maintainer; for auto scrubbing, use preferred NCL maintainer.

**Routine Maintenance:** Dust mop using mop treated with an NCL dust mop treatment. Damp mop or clean with an automatic scrubber using your preferred NCL neutral floor cleaner following label directions.

**Scrub and Recoat:** When routine maintenance and buffing/ burnishing no longer responds as needed, scrub and recoat using an NCL scrub and recoat cleaner following label directions.

### SPECIFICATIONS

Type .....	Integrated latex & oligomeric polymer	Recoatability .....	Excellent
pH .....	8.2 ± 0.2	Removability .....	Excellent
Drying time (minutes) .....	20	Durability .....	Superior
Odor .....	Pleasant	Soil Resistance .....	Superior
Color .....	White, opaque	Scuff Resistance .....	Superior
Film .....	Clear, non-yellowing	Black Mark Resistance .....	Superior
Freeze thaw stable .....	Yes	Deep Gloss Appearance .....	Superior
Flash Point .....	None	Slip Resistance .....	Excellent
Powdering .....	Nil	High Speed Burnishing .....	Excellent
Detergent Resistant .....	Yes (after 24 hr.)	Shelf Life .....	1 year minimum in original unopened container
Leveling .....	Superior		

### SAFETY INFORMATION

**KEEP OUT OF THE REACH OF CHILDREN.**

#### Precautionary statement

**Prevention:** Observe good industrial hygiene practices.

**Response:** Wash thoroughly after handling.

**Storage:** Store away from incompatible materials.

**Disposal:** Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at [www.nclonline.com](http://www.nclonline.com)

**KEEP FROM FREEZING**

For Commercial and Industrial Use Only



FLOOR CARE



Floor Coating and Finishing Material  
As to Slip Resistance Only  
18EL



401 N. 10th Street • Philadelphia, PA 19123  
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517  
[www.nclonline.com](http://www.nclonline.com) • e-mail:[info@nclonline.com](mailto:info@nclonline.com)