



# WORLD CLASS

## Ultra High Speed Sealer / Finish

### DESCRIPTION

Utilizing Integrated Fusion Polymer (IFP) technology, this revolutionary floor coating offers the perfect balance of deep wet look gloss with extended gloss retention and exceptional film wearability. IFP technology provides a "tightness" or density to the polymer system that is significantly greater than conventional high speed floor finishes. Because of the enhanced gloss retention of this ultra high speed product, daily burnishing is not required to maintain the maximum gloss. One or two burnishings per week in heavy traffic areas is all that is required to maintain a deep, brilliant gloss. This product is the ideal choice for any ultra high speed maintenance program.

### PRODUCT FEATURES / BENEFITS

- Sealer / Finish / Simplifies floor care system
- Immediate deep wet look gloss / Dazzling gloss without burnishing
- Long term gloss retention / Less maintenance needed to keep original lustre
- Utilizes IFP technology / Enhances durability & maximizes resistance to soiling, black heel marks and scuffing
- Enhanced leveling / Easy to use by any service personnel

### DIRECTIONS FOR USE

Integrated fusion polymer technology has led to the creation of a very tough, long lasting sealer/finish with a flexible film offering outstanding buffability by high speed buffing or ultra high speed burnishing. Gives outstanding performance on all types of resilient flooring including vinyl, VAT, and vinyl composition tile, also for terrazzo, asphalt, stone and quarry tile and other hard surface floors.

#### This revolutionary sealer/finish exhibits:

- instant deep wet look
- long term gloss retention
- black mark resistant
- excellent dirt release
- extended restoration cycles
- outstanding leveling
- superior durability
- easy repairability
- user friendly formula

**Floor Preparation:** Strip old finish and wax using your preferred NCL floor stripper following label directions. For baseboards and corners, use an NCL baseboard stripper following label directions. If necessary, rinse thoroughly with clean water and allow to completely dry.

**Application:** Using a clean mop or applicator apply a thin uniform coat of WORLD CLASS™ Ultra High Speed Sealer / Finish. Allow to dry for a minimum of 30 minutes after each coat. Do not apply more than 4 coats in a 24 hour period. Floor should be thoroughly dry before traffic is allowed in area.

**High Speed Buffing and Burnishing:** WORLD CLASS™ Ultra High Speed Sealer / Finish is an ideal product for use with high speed polishing or burnishing machines of 1000 rpm or higher. Prior to buffing or burnishing dust mop the floor surface using an NCL dust mop treatment. Buff or dry burnish using an approved buffing pad. For spray buffing, mop-on or autoscubber restoring use a preferred NCL gloss restorer.

**Routine Maintenance:** Dust mop using mop treated with an NCL dust mop treatment. Damp mop or clean with an automatic scrubber using your preferred NCL neutral floor cleaner following label directions.

**Scrub and Recoat:** When routine maintenance and buffing/burnishing no longer responds as needed, scrub and recoat using an NCL scrub and recoat cleaner following label directions.

### SPECIFICATIONS

Type .....	Integrated Fusion Polymer
Color .....	White, opaque liquid
Odor .....	Typical acrylic
pH .....	8.2 ± 0.3
Drying Time (minutes) .....	30
Specific Gravity (g/cc) .....	1.03 ± 0.01
Density (lbs/gal) .....	8.6 ± 0.1
Slip Resistant .....	Yes

Freeze Thaw Stable .....	Yes (3 cycles)
Detergent Resistant .....	Yes
Leveling .....	Excellent
Black Mark Resistant .....	Excellent
Scuff Resistant .....	Excellent
Resistant to Soiling .....	Excellent
Gloss Retention .....	Excellent
Immediate Wet Look Gloss .....	Outstanding
Shelf Life .....	1 year minimum in original unopened container

### SAFETY INFORMATION

**KEEP OUT OF THE REACH OF CHILDREN.**

#### Precautionary statement

**Prevention:** Observe good industrial hygiene practices.

**Response:** Wash thoroughly after handling.

**Storage:** Store away from incompatible materials.

**Disposal:** Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### Additional safety measures:

Read the entire label and SDS before using this product, and for additional first-aid measures. SDS for this product is available on the web at [www.nclonline.com](http://www.nclonline.com)

**KEEP FROM FREEZING**

For Commercial and Industrial Use Only



FLOOR CARE



Floor Coating and Finishing Material  
As to Slip Resistance Only  
18EL



World Class Cleaning & Hygiene Solutions™

401 N. 10th Street • Philadelphia, PA 19123  
1-800-NAT-CHEM • 215-922-1200 • FAX: 215-922-5517  
[www.nclonline.com](http://www.nclonline.com) • e-mail:[info@nclonline.com](mailto:info@nclonline.com)



TDS-0570-0623